

SAFETY DATA SHEET

S-8900 PART A	SDS Number : S-8900A	Revision Date: 08/18/2015
----------------------	-----------------------------	----------------------------------



1. PRODUCT AND COMPANY IDENTIFICATION:

Product Name: S-8900 A

Product Code: S-8900A

Product Use: Solventborne Concrete Sealer Component

Synonyms: Solventborne Aliphatic Polyisocyanate

Chemical Formula: Solventborne Aliphatic


Polyisocyanate Restrictions: Institutional, Commercial and Retail Concrete and Masonry Use Only

Manufactured For: KoolCote
 4674 Priem Ln Ste 104
 Pflugerville TX 78660
 512.251.5740 / 512.251.5722
www.koolcote.com

Emergency contact: Chemtrec 800.424.9300

2. HAZARD IDENTIFICATION:

GHS CLASSIFICATION:

<u>HEALTH</u>	<u>ENVIRONMENTAL</u>	<u>PHYSICAL</u>
<p><i>Skin Irritation: Category 2</i> <i>Eye Irritation: Category 2A</i> <i>Specific target organ toxicity, single exposure: Category 3 (Respiratory System, CNS)</i> <i>Specific target organ toxicity, repeated exposure : Category 2 (Liver, Kidneys, CNS)</i> <i>Aspiration Hazard: Category 1</i></p>	<p><i>Acute Toxicity: None Known</i> <i>Chronic Toxicity: None Known</i></p>	<p><i>Flammable Liquid: Category 3</i></p>
<p><u>GHS Pictogram</u></p> 	<p><u>Signal Word:</u> Danger</p>	
<p><u>Hazard Statements</u></p> <p>Flammable Liquid and Vapor Causes skin irritation Causes serious eye irritation Harmful if inhaled May cause respiratory irritation May cause drowsiness or dizziness May cause damage to organs (Lungs) through long or repeated exposure if inhaled. May be fatal if swallowed or enters airways.</p>		
<p><u>Precautionary Statements</u></p> <p>Obtain special instructions before use. Keep away from heat/sparks/open flames /hot surfaces. No smoking. Take precautionary measures against static discharge. Wear respiratory protection/protective gloves/protective clothing/eye protection/face protection. Do not breathe mists, vapors or spray.</p>		

SAFETY DATA SHEET

S-8900 PART A

SDS Number : S-8900A

Revision Date: 08/18/2015

IF IN EYES: Rinse with water for several minutes. Remove contact lenses, if present and easy to do. If irritation occurs and persists, get medical attention.

IF ON SKIN: Remove immediately all contaminated clothing. Rinse skin with water for several minutes. Wash contaminated clothing before reuse. If irritation occurs and persists, get medical attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Severe asthmatic reactions can occur in sensitized individuals. Get medical attention immediately. Administer oxygen or artificial respiration as necessary. Asthmatic symptoms may have a delayed onset.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison center.

Keep container tightly closed. Store in a well ventilated place.

Dispose of contents/container in accordance with local regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS:

INGREDIENT	CAS NO.	PERCENT	HAZARDOUS
HEXYLENE GLYCOL	107-41-5	7-23%	YES
N-BUTYL ACETATE	123-86-4	15-20%	YES
MIXED XYLENES	1330-20-7	10-12%	YES
ETHYLBENZENE	100-41-4	0.1-1.5%	YES
Exact Percentages are being withheld as trade secret information.			

4. FIRST-AID MEASURES:

Eye Contact: Rinse with water for 15 minutes. Remove contact lenses, if present and easy to do. If irritation occurs and persists, get medical attention.

Skin Contact: Remove immediately all contaminated clothing. Rinse skin with water for several minutes. Wash contaminated clothing before reuse. If irritation occurs and persists, get medical attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately. Administer oxygen or artificial respiration as necessary.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison center.

5. FIRE-FIGHTING MEASURES:

Unusual Fire Explosion Hazards: In poorly ventilated areas, vapors may accumulate and travel to locations distant to the work area. Be aware of any flame or spark sources which could ignite vapors near and in range of the work area.

Fire Extinguishing media: Use dry chemical, carbon dioxide or alcohol-resistant foam.

Hazards during fire-fighting:

Containers may rupture when exposed to extreme heat.

Protective equipment for fire-fighting:

Wear NFPA-approved self-contained breathing apparatus, helmet, hood, boots and gloves.

SAFETY DATA SHEET

S-8900 PART A

SDS Number : S-8900A

Revision Date: 08/18/2015

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions:

Use recommended personal protective clothing and equipment, including eye protection, chemically resistant gloves and vapor respirator. To prevent slipping, do not walk through spilled material.

Environmental precautions:

Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off of work area, and material should be absorbed, collected and disposed of in accordance with regulations. Keep product from entering storm drains. Consult local and federal guidelines for proper disposal of these materials.

Cleanup:

General: In poorly ventilated areas, vapors may accumulate and travel to locations distant to the work area. Be aware of any flame or spark sources which could ignite vapors near and in range of the work area. Eliminate all ignition sources in the immediate area. Use clean non-sparking tools for spill cleanup.

- For small amounts of released material: Absorb or cover with inert absorbent, sand or dry earth. Transfer to a metal or HDPE container for disposal. - For large amounts of released material: Dike around spilled material with absorbent to contain. Absorb or cover with inert absorbent, sand or dry earth. Transfer to a metal container for disposal.

7. HANDLING and STORAGE:

Handling:

General advice - No specific measures are necessary provided product and recommended protective clothing/equipment are used correctly. Do not generate and breathe mists, vapors or fine spray. May only be mixed with Surtec Surpro HS Part B. Do not mix with other chemicals. This is a commercial product, not intended for home use. Keep out of reach of children.

Storage:

General advice - Protect against physical damage. Store in a cool, well ventilated area. Store in a tightly closed container.

Shelf Life:

12 months minimum

8. EXPOSURE CONTROLS and PERSONAL PROTECTION:

Advice on system design:

Provide local exhaust ventilation to control vapors for published exposure limits.

Personal protective equipment (HMIS rating 'I'):

Eye protection: Wear safety glasses with side shields or safety goggles to prevent exposure or full face shield if splash hazard exists.

Skin protection: Chemical-resistant gloves. Wear appropriate protective clothing to prevent possible skin contact.

Respiratory protection: Product is not intended for airless or other paint spray application. Do not breathe mists, vapors or spray. Use proper NIOSH-OSHA respirator fitted with proper cartridges if mists are generated, ventilation is inadequate or exposure limits are exceeded.

General safety and hygiene measures: Exercise stringent hygiene practices to minimize exposure. If contact occurs, wash any body part with soap and water immediately. Wash hands after use, and before eating, drinking or smoking.

Other protective measures:

Nearby running water on the job site is necessary, should an accident occur.

Exposure Guidelines:

ACGIH TLV: 150 ppm (123-86-4), 100 ppm (1330-20-7), 20 ppm (100-41-4)
STEL: 200 ppm (123-86-4), 150 ppm (1330-20-7), 125 ppm (100-41-4)
OSHA PEL: 150 ppm (123-86-4), 100 ppm (1330-20-7), 100 ppm (100-41-4)

SAFETY DATA SHEET

S-8900 PART A	SDS Number : S-8900A	Revision Date: 08/18/2015
----------------------	-----------------------------	----------------------------------

9. PHYSICAL and CHEMICAL PROPERTIES:

Appearance:	Clear Liquid	Flash Point:	82° F C.O.C.
Odor:	Solvent	Upper/Lower Flammability Limits:	No information available
pH value:	No information available	Relative Density (water):	1.00
Specific gravity:	1.00 (H2O = 1)	Auto-Ignition Temperature:	No information available
Solidification temperature:	No information available	Decomposition temperature:	No information available
Freezing/Melting point:	No information available	Partition Coefficient	No information available
Boiling point:	No information available	Odor Threshold	No information available
Vapor density:	No information available	Viscosity:	~200 cps.
Vapor pressure:	No information available	Partition Coefficient	No information available
Evaporation Rate:	No information available	Solubility in water:	None
Regulatory VOC:	<400 g/l		

10. STABILITY and REACTIVITY:

Conditions to avoid: Heat, flame, sparks.

Substances to avoid: Oxidizers, water.

Hazardous reactions: Product is stable under normal conditions of use and storage.

Decomposition or By-products: In fire conditions: carbon monoxide (CO), carbon dioxide (CO₂).

11. TOXICOLOGY INFORMATION:

Acute Toxicity (Symptoms):

Oral: Ingestion may cause pain, nausea, vomiting, and diarrhea.

Eye irritation: Irritation, redness, tearing and swelling. May cause temporary corneal injury.

Skin irritation: Irritation, redness, itching and swelling.

Inhalation: Inhalation of vapors may cause irritation to the respiratory tract with runny nose, sore throat, coughing and difficulty breathing.

Sensitization: Skin: No. Respiratory: No

Aspiration Hazard: May be fatal if swallowed or enters airways.

Target Organ Effects - Single Exposure: (Respiratory System): May cause respiratory irritation; **(Central Nervous System):** May cause drowsiness or dizziness.

Chronic Toxicity:

Target Organ Effects - Repeated Exposure: May cause damage to organs (liver, kidney and central nervous system) through prolonged or repeated exposure

Carcinogenicity: No human carcinogenic substances as defined by ACGIH, NTP and/or OSHA. IARC classifies Ethylbenzene (100-41-4) as Group 2B: Possibly carcinogenic to humans. ACGIH classifies Ethylbenzene as a confirmed animal carcinogen with unknown relevance to humans. Product not classifiable as a human carcinogen.

SAFETY DATA SHEET

S-8900 PART A

SDS Number : S-8900A

Revision Date: 08/18/2015

12. ECOLOGICAL INFORMATION:

Biodegradation:

Test method: Unspecified

Analysis method: Unspecified

Degree of elimination: Not readily biodegradable.

Environmental toxicity:

Acute and prolonged toxicity to fish: Not available

Toxicity to microorganisms: Not available

Other ecotoxicological information: Not available

13. DISPOSAL CONSIDERATIONS:

Waste disposal of substance: Dispose of in accordance with all Federal, State and Local regulations when storing and disposing of substances. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA (EPA regulations for hazardous waste).

Container disposal: Dispose of in a licensed facility in accordance with local regulations.

RCRA:

Unspecified.

14. TRANSPORTATION INFORMATION:

DOT:

UN/ID No: 1263

Proper Shipping Name: PAINT (FLASH POINT > 73°F)

Hazard Class: 3

Packing Group: III

15. REGULATORY INFORMATION:

Federal Regulations:

Registration status:

TSCA, US:

All components are listed or exempt.

SARA hazard category (EPCRA 311/312):

Fire hazard

Acute health hazard

Chronic health hazard

SARA TITLE III, SECTION 313:

CAS Number: _____ Chemical Name:

1330-20-7 Mixed Xylenes

100-41-4 Ethylbenzene

SAFETY DATA SHEET

S-8900 PART A

SDS Number : S-8900A

Revision Date: 08/18/2015

State Regulations:

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

CAS Number: _____ Chemical Name:

100-41-4	Ethylbenzene
108-88-3	Toluene (trace)
71-43-2	Benzene (trace)

16. OTHER INFORMATION:

NFPA Rating:


Health: 2 Fire: 3 Reactivity: 0 Special Hazard: none

HMIS Rating:

Health: 2 Flammability: 3 Physical Hazard: 0
Personal Protection: B or I (safety glasses with side shields, chemical-resistant gloves and vapor respirator (if necessary))

Both NFPA and HMIS III rating systems use a numbering scale that ranges from 0 to 4 to indicate the degree of hazard. A value of zero means the substance possesses no hazard while a value of four indicates high hazard.

NFPA Rating



HMIS Rating

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

Prepared: 08/18/2015 **Revision No.:** Original

Local Contact Information:

KoolCote
512.251.5740
www.koolcote.com

Notice: The information provided is accurate to the best of our knowledge and is offered in good faith. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in specific context of the intended use and determine whether they are appropriate.

Warranty: This is a proprietary KoolCote product, warranted to be of uniform quality within our stringent manufacturing tolerances. As no control is exercised over product use, no warranty is made as to the effects of such use (neither expressed nor implied). Obligation of the seller and manufacturer under this warranty shall be limited to a refund of the purchase price of that portion of the material proven to be defective. The user assumes all other risk and liability resulting from uses of this product. Contact KoolCote with any questions regarding this policy.